## **©OUTLANDER™ MAX XT-P 1000R™**

## PACKAGE HIGHLIGHTS

- Rotax® V-twin engine
- Front and rear FOX<sup>†</sup> 1.5 PODIUM<sup>†</sup> QS3 shocks
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 1,361 kg WARN† winch with roller fairlead
- 14-in. cast-aluminum beadlock wheels
- 26-in. ITP<sup>†</sup> Terracross radial tires
- Painted plastics for premium look
- Heavy-duty front and rear bumpers
- Aluminum taper-profile handlebar with wind deflectors and square pad

- Multifunction Analog / Digital gauge
- Convertible Rack System (CRS) with LinQ<sup>™</sup> system
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips



Triple Black

ENGINES	1000R
Туре	89 hp, Rotax 976 cc V-twin, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok‡ QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Double A-arm 22.9 cm travel
Front Shocks	FOX 1.5 PODIUM QS3
Rear Suspension	Torsional Trailing arm Independent (TTI) 23.6 cm travel
Rear Shocks	FOX 1.5 PODIUM QS3

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEELS	
Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)
Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14-in. cast-aluminum beadlock

DIMENSIONS / C	CAPACITIES
LxWxH	238.8 x 116.8 x 135 cm
Wheelbase	149.9 cm
<b>Ground Clearance</b>	27.9 cm
Seat Height	87.7 cm
Dry Weight*	381 kg
Rack Capacity	Front: 45 kg Rear: 90 kg
Storage Capacity	Rear: 21.4 L
Towing Capacity	590 kg
Fuel Capacity	20.5 L

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Convertible Rack System (CRS)
Winch	1,361 kg WARN winch with roller fairlead	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Heavy-duty front & rear bumpers, aluminum taper-profile handlebar with wind deflectors and square pad		

WARRANTY	
Factory	2 years
Extended	Up to 36 months B.E.S.T. coverage



