

2018 OUTLANDER™ PRO 450

HIGHLIGHTS

- Rotax® single cylinder engine
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- 12-in. cast-aluminum wheels
- 26-in. 6-ply Carlisle† ACT HD radial tires
- Reinforced seat skin
- Relocated air intakes
- Increased ground clearance
- NEW Digitally Encoded Security System (D.E.S.S.™)
- 590 kg towing capacity
- 500-W magneto
- Multifunction digital gauge
- Steel racks LinQ quick-attach accessory system and a combined 163.3 kg capacity
- 10.9 L water-resistant rear compartment



Green

ENGINES

450

Type	38 hp, Rotax 427 cc single cylinder, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE† auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Double A-arm 22.9 cm travel
Front Shocks	Oil
Rear Suspension	Torsional Trailing arm Independent (TTI) 22.4 cm travel
Rear Shocks	Oil

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	Prewired for available winch	Lighting	70-W from dual 35-W front light / brake light
Protection	N/A	Seat	Reinforced seat skin
		Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)

WARRANTY

Factory	2 years
Extended	Up to 36 months B.E.S.T. coverage

TIRES / WHEELS

Front Tires	Carlisle† ACT HD 26 x 8 x 12-in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle† ACT HD 26 x 10 x 12-in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / CAPACITIES

L x W x H	211 x 116.8 x 124 cm
Wheelbase	129.5 cm
Ground Clearance	29.2 cm
Seat Height	85.8 cm
Dry Weight*	308 kg
Rack Capacity	Front: 54.4 kg Rear: 109 kg
Storage Capacity	Rear: 10.9 L
Towing Capacity	590 kg
Fuel Capacity	20.5 L

BEST PROTECTION ©2017 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP US Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext. 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

can-am

Can-AmOffroad.com

