

2018 RENEGADE[®] X[®] mr 1000R

HIGHLIGHTS

- Rotax[®] snorkeled V-Twin engine with relocated CVT intake and outlet
- Front and rear FOX⁺ QS3 shocks
- 30-in. ITP Cryptid⁺ tires
- 14-in. cast-aluminum beadlock wheels
- 1,361 kg WARN⁺ winch with roller fairlead
- Aluminum skid plate
- Heavy-duty front and rear bumpers
- Continuously Variable Transmission (CVT) with Extra Low L-Gear
- Aluminum taper-profile handlebar with grab handle, wind deflectors and square pad
- Tri-Mode Dynamic Power Steering (DPS[™])
- Torsional Trailing arm Independent (TTI) rear suspension
- Mudguards
- Multifunction digital gauge
- Painted plastics for premium look
- X-package coloration, graphics and seat cover



■ Carbon Black & Sunburst Yellow

ENGINE	1000R
Type	89 hp, Rotax 976 cc V-twin, snorkeled, liquid cooled
Fuel Delivery System	Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE ⁺ auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Double A-arm
Front Shocks	FOX 1.5 PODIUM QS3
Rear Suspension	Torsional Trailing arm Independent (TTI)
Rear Shocks	FOX 1.5 PODIUM QS3

BRAKES

Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHEELS

Front Tires	ITP Cryptid ⁺ 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Rear Tires	ITP Cryptid ⁺ 30 x 9 x 14 in. (76.6 x 22.9 x 35.6 cm)
Wheels	14-in. cast-aluminum beadlock

DIMENSIONS / CAPACITIES

L x W x H	224 x 127 x 131 cm
Wheelbase	129.5 cm
Ground Clearance	31.8 cm
Seat Height	93.3 cm
Dry Weight	441 kg
Rack Capacity	Rear: 16 kg
Storage Capacity	N/A
Towing Capacity	590 kg
Fuel Capacity	20.5 L

FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
Winch	1,361 kg WARN winch with roller fairlead	Lighting	240 W from 4 fender mounted projector beam headlamps (60 W) with tail light / brake light
Protection	Front & rear bumpers, aluminum taper-profile handlebar with grab handle, wind deflectors and square pads, aluminum skid plate, mudguards	Seat	Standard
		Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)

WARRANTY

Factory	2 years
Extended	Up to 36 months B.E.S.T. coverage

BEST PROTECTION ©2017 Bombardier Recreational Products Inc (BRP). All rights reserved.™, ® and the BRP logo are registered trademarks of BRP or its affiliates. Products are distributed in the U.S.A. by BRP U.S. Inc. *Base model dry weight shown. †Visco-Lok is a trademark of GMI Viscodrive GmbH. All other trademarks are the property of their respective owners. Because of our ongoing commitment to product quality and innovation, BRP reserves the right at anytime to discontinue or change specifications, price, design, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all ATV drivers take a training course. For safety and training information, see your dealer or, in U.S.A. call the ATV Safety Institute at 1 (800) 887-2887. In Canada, call the Canadian Safety Council at 1 (613) 739-1535 ext. 227. ATVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Always remember that riding and alcohol / drugs don't mix. Never ride on paved surfaces or public roads. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. ATVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any ATV not specifically designated for such use.

can-am.

Can-AmOffroad.com

