

2018 TRAXTER DPS™ HD8

HIGHLIGHTS

- Heavy-duty Rotax® V-Twin engine
- PRO-TORQ transmission
- Dynamic Power Steering (DPS™)
- Lockable rear differential and Visco-Lok® QE auto-locking front differential
- TTA-HD rear suspension
- 14-in. cast-aluminum wheels with 27-in. Maxxis Bighorn 2.0¹ tires
- 39.5 L of storage capacity including a 6.3 L water-resistant toolbox
- VERSA-PRO bench seat
- Multifunction cargo box with sturdy tailgate
- Central skid plate
- Multifunction digital gauge
- 1-year maintenance free and easy access to key maintenance components



Green

ENGINES

ENGINES	HD8
Type	50 hp, Rotax 799.9 cc, V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PRO-TORQ transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	True 4-mode traction system: 2x4 open rear dif., 2x4 locked rear dif., 4x4 open rear dif., 4x4 locked rear dif. Visco-Lok QE auto-locking front dif.
Driving Assistance	Electronic Hill Descent Control
Power Steering	Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Double A-arm / 25.4 cm travel
Front Shocks	Twin tube gas charged shocks
Rear Suspension	TTA-HD with external sway bar / 25.4 cm travel
Rear Shocks	Twin tube gas charged shocks

BRAKES

Front	Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm ventilated disc brakes with hydraulic single-piston calipers

TIRES / WHEELS

Front Tires	Maxxis Bighorn 2.0 27 x 9 x 14 in. (68.6 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 27 x 11 x 14 in. (68.6 x 27.9 x 35.6 cm)
Wheels	14-in. cast-aluminum

FEATURES

Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, seat belt, diagnostics, clock, auto shut off	Lighting	140-W lighting output from four 35-W reflectors ensuring a wide visibility and LED tail lights
Battery	12 V (18 amp/h)	Winch	N/A
Magneto	650 W	Seat	VERSA-PRO bench seat with passenger seats flipping up, underside hooks and contoured bench to improve entrance/exit of the cab
Instrumentation	Lighter type DC outlet in console (20-A)	Protection	Integrated front steel bumper, central skid plate
		Hitch Type	2-in. hitch receiver
		Steering Wheel	Adjustable tilt steering

WARRANTY

Factory	2 years
Extended	Up to 30 months B.E.S.T. coverage

DIMENSIONS / CAPACITIES

L x W x H	305 x 157.5 x 193 cm
Wheelbase	211.5 cm
Ground Clearance	28 cm
Estimated Dry Weight	646.4 kg
Cage	ROPS-approved profiled cage. Certified ISO 3471 and OSHA.
Cargo Box Dimensions	96.5 x 138.4 x 30.5 cm
Cargo Box Capacity	454 kg
Tailgate Load Capacity	113.4 kg
Storage Capacity	Total: 39.5 L Under dash: 22.8 L Dash: 6.9 L Water-resistant and removable toolbox: 6.3 L Armrests and cup holders: 3.5 L
Towing Capacity	907.2 kg
Payload Capacity	680 kg
Fuel Capacity	40 L
Person Capacity	3



©2017 Bombardier Recreational Products Inc (BRP). All rights reserved.™ ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.

can-am



Can-AmOffroad.com